

DUAL STAGE MICRO REGULATOR

WARNING - READ BEFORE USING

1. **For CO2 Use Only** - Not for use with argon or nitrogen gas.
2. **Avoid excessive heat** - Operate at temperatures of 100° F. or lower.
3. **Keep Away From Children**

Packing List:

- 1 D61A Regulator
- 1 D10 Swivel
- 1 D56 74 Gram Adapter
- 1 B11 Grey Gas Ball Lock Fitting

Choose Your CO2 Cartridge

This unit comes with a 16 gram threaded (3/8 - 24 threads) CO2 adapter installed in the regulator, and a 74 gram threaded (5/8 - 18 threads) CO2 adapter. To



convert from 16 gram threaded to 74 gram threaded, use a 7/8" wrench (not included) and remove the bottom adapter, being careful to leave the clear molded sealing gasket inside. Now screw in the larger adapter firmly and your regulator is set up for 74 gram cartridges.

Instructions

1. First, install on the included grey gas fitting, and hand tighten till very snug (the white O ring in the fitting will seal the gas).
2. Make sure the dispensing knob is fully counterclockwise (in the off position). Now screw in the CO2 cartridge you are using quickly to avoid wasting CO2 when the cartridge is first pierced.
3. Now adjust your dispensing pressure with the dial on top of the knob (usually 5 - 10 PSI).

WARNING - Never unscrew a CO2 cartridge until you are certain it is empty. Keep away from children.

This regulator features two stages for more accuracy - an initial higher pressure chamber from the CO2 feed in the base, and a lower pressure second chamber higher up that feeds the adjustment knob. The result - more accuracy and finer pressure control.

brewersedge.com • info@brewersedge.com

Final Inspection by #5