

MALE FLARE MICRO REGULATOR

WARNING - READ BEFORE USING

1. **For C02 Use Only** - Not for use with higher pressure argon or nitrogen gas.
2. **Avoid excessive heat** - Operate at temperatures of 100° F. or lower.

Packing List:

- 1 D55A Regulator with L12 flare
- 1 74 Gram Adapter
- 1 Extra Sealing Washer
- 1 Burst Disk Repair Kit
- 1 D87 White Concave Washer

Choose Your C02 Cartridge

This unit comes with a 16 gram threaded (3/8 - 24 threads) C02 adapter installed in the regulator, and a 74 gram threaded (5/8 - 18 threads) C02 adapter. To convert from 16 gram threaded to 74 gram threaded, use a 7/8" wrench (not included) and remove the bottom adapter, being careful to leave the clear molded sealing gasket inside. Now screw in the larger adapter firmly and your regulator is set up for 74 gram cartridges.



Instructions

1. First, install on a threaded 1/4" female flare gas line, being sure to insert the white D87 Concave Sealing Washer into the female flare before tightening to seal.
2. Make sure the dispensing knob is fully counterclockwise (in the off position). Now screw in the C02 cartridge you are using quickly to avoid wasting C02 when the cartridge is first pierced.
3. Now adjust your dispensing pressure with the dial on top of the knob (usually 4 - 8 PSI). A check valve is built into the regulator to keep fluids from backing up into the regulator.



WARNING - Never unscrew a C02 cartridge until you are certain it is empty. Keep away from children.

brewersedge.com • info@brewersedge.com