

## 0-30 PSI SODASTREAM® REGULATOR

### WARNING - READ BEFORE USING

1. **Secure upright when in use** - If the Regulator is allowed to fall on its side attached to a full tank, the liquid CO<sub>2</sub> could escape so fast that it will rupture your keg, causing it to explode.
2. **For CO<sub>2</sub> Use Only** - Not for use with higher pressure argon or nitrogen gas. KEEP AWAY FROM CHILDREN.
3. **Avoid excessive heat** - Operate at temperatures of 100° F. or lower.

### Instructions

1. To use your CO<sub>2</sub> Regulator, first install a gas outlet on the right side. This can be any male 1/8" NPT or 1/8" BSP thread outlet.

1a. If the outlet is metal like William's item L38, be sure to use teflon tape or pipe leak paste on the threads to prevent leaks.

1b. If it is a plastic Duotight compatible fitting, teflon tape is not needed. Tighten finger tight and then tighten ¼ turn with a wrench to seal.

2. With the black knob fully counter clockwise, screw a Sodastream® cylinder into the base, and tighten. Then turn the knob clockwise to adjust the dispensing pressure. If gas does not come out, make sure the regulator is *firmly* tightened on the tank - try using a towel to increase your grip if needed.



[williamsbrewing.com](http://williamsbrewing.com) • [help@williamsbrewing.com](mailto:help@williamsbrewing.com)

800-759-6025

Final Inspection by #1

G20